

MR[®] 70 I AMS Developer



Product Characteristics

- Developer for penetrant testing acc. to EN ISO 3452:2
- Carrier medium Solvent
- Very easy removable from the surface
- QPL SAE AMS 2644 for red-white-testing

Minimum shelf life / Temperatures

Aerosol / Bulk:
3 years at storage temperature
Storage: + 5 °C - + 45 °C
Application: - 10 °C - + 50 °C
(- 30 °C - + 50 °C with MR[®] 312, MR[®] 79, MR[®] 85, MR[®] 88)



Approvals / Specification



- EN ISO 3452-2
- ASME Code V, Art. 6
- QPL SAE AMS 2644
- ASTM E1417
- ASTM E165
- RCC-M
- ASME

Further Information

Process description according to EN ISO 3452-1 and AMS 2644 on request or on www.mr-chemie.de/en. For further information see Material Safety Data Sheet and certificate 3.1. For additional equipment please visit our Homepage or contact our sales team.

Suggested Products

Pre-Cleaner: MR[®]71, MR[®] 79, MR[®] 85, MR[®] 88, MR[®] 3001, MR[®]
Penetrant: 3002
Remover: All penetrants type I, II & III (except "Hot" and AMS)
Test block: MR[®] 79, MR[®] 85, MR[®] 88, Water
Reference testblock 1 and 2, ASTM testblock

Delivery Form



technical changes reserved!